



(12) **United States Patent**  
**Lee et al.**

(10) **Patent No.:** **US 9,636,075 B2**  
(45) **Date of Patent:** **May 2, 2017**

(54) **SIMULATION-BASED ESTIMATION OF ELASTICITY PARAMETERS AND USE OF SAME FOR NON-INVASIVE CANCER DETECTION AND CANCER STAGING**

(52) **U.S. Cl.**  
CPC ..... *A61B 6/5217* (2013.01); *A61B 6/032* (2013.01); *A61B 6/466* (2013.01); *A61B 6/50* (2013.01);

(Continued)

(71) Applicant: **The University of North Carolina at Chapel Hill**, Chapel Hill, NC (US)

(58) **Field of Classification Search**  
None  
See application file for complete search history.

(72) Inventors: **Huai-Ping Lee**, Plantation, FL (US); **Mark Stephen Foskey**, Chapel Hill, NC (US); **Marc Niethammer**, Carrboro, NC (US); **Ming Lin**, Chapel Hill, NC (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2002/0137014 A1 9/2002 Anderson et al.  
2007/0239409 A1 10/2007 Alan

(Continued)

(73) Assignee: **THE UNIVERSITY OF NORTH CAROLINA AT CHAPEL HILL**, Chapel Hill, NC (US)

OTHER PUBLICATIONS

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 254 days.

Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration for International Application No. PCT/US2013/053803 (Nov. 1, 2013).

(Continued)

(21) Appl. No.: **14/420,239**

*Primary Examiner* — Joseph M Santos Rodriguez

(22) PCT Filed: **Aug. 6, 2013**

(74) *Attorney, Agent, or Firm* — Jenkins, Wilson, Taylor & Hunt, P.A.

(86) PCT No.: **PCT/US2013/053803**

§ 371 (c)(1),

(2) Date: **Feb. 6, 2015**

(57) **ABSTRACT**

(87) PCT Pub. No.: **WO2014/025791**

PCT Pub. Date: **Feb. 13, 2014**

Simulation-based estimation of elasticity parameters and use of same for non-invasive cancer detection and cancer staging are disclosed. According to one aspect, a method for simulation-based estimation of elasticity parameters includes constructing a 3D model of an object comprising biological tissue, the model having a first shape and an elasticity value. A simulation iteration is then performed, which includes simulating the application of an external force to the model, causing the model to have a second shape, measuring the difference between the second shape and a target shape, and determining whether the measured difference between the second shape and the target shape is within a threshold of error. If the measured difference is not within the threshold of error, the process performs additional

(Continued)

(65) **Prior Publication Data**

US 2015/0216496 A1 Aug. 6, 2015

**Related U.S. Application Data**

(60) Provisional application No. 61/680,116, filed on Aug. 6, 2012.

(51) **Int. Cl.**

*A61B 6/06* (2006.01)

*A61B 6/00* (2006.01)

(Continued)

